

## Hubble Lithium Blade 51V 10KW



1.5C Rating. Built-in Cloud Monitoring. Featuring Blade cells – the safest in the industry 10 Year Unlimited Cycle Warranty. Parallel up to 15 units with full comms

Rating: Not Rated Yet

### Price

Normal price: R 52900

Price: R 44999

[Ask a question](#)

Manufacturer [Hubble](#)

### Description

[Blade Brochure](#) | [Blade Warranty](#)

## Features

- Smart LED Status Bar
- High cycle and service life
- Internet enabled cloud monitoring
- Firmware updates over the internet
- 1.5C Industry leading battery performance
- 16 Cell LiFePO4 Graphite Blade battery system
- Includes wall-mount brackets for easy wall mounting

- Internal wiring cable compartment for safer and easier installs
- Parallel up to 15 batteries with full communications and monitoring
- CAN Bus fully integrates and communicates with leading inverter brands

### Technical Specifications

- Rated Capacity (5HR): 137Ah
- Nominal Voltage: 51.2V
- Design Capacity: 7kWh 10kW
- Equalized Charge Voltage: 55.8V
- Max. Continuous Charging Current: 140A
- Max. Continuous Discharging Current: 200A
- C Rating: 1.5C
- Weight: Approx. 64kg
- Monitoring: Wi-Fi enabled remote monitoring
- Parallel: Parallel connection up to 15 packs with full communications
- Dimensions (WxDxH): 1125 mm x 175 mm x 340 mm
- Ports: 1 x CAN-bus, 2 x Battery Link Ports, 1 x Expert Inverter Port
- Cells: 16 cells. New Li-ion LiFePO4 Blade Prismatic Cells
- Design Life: ± 15 Years
- Cycle Life: UNLIMITED CYCLES WITHIN THE HUBBLE LITHIUM 10 YEAR WARRANTY. (Ts & Cs Apply)
- Certification: CE, UN38.3
- Outer Package Material: White Bake Lacquer Steel Case
- Operating Temperature
  - Charging: -20°C to +55 °C
  - Discharging: -30°C to +55 °C
  - Storage: -30 to +55°C
- Protection: Electronic Circuit Breaker, BMS Over/Under Voltage Protection, Current Limiting

### Reviews

Write a review for this product & receive a free discount coupon as well as access to exclusive member content. Please [register](#) or [login](#) to write your review.